

Area of Application:
Bench mounted
Water

Max. working pressure 10 bar
Temperature range 5°C-65°C

Details:
Rubber sealed headwork open/close 2x360°
3-Zone colour, acc. to EN13792:2002
BROEN-LAB Polyester powder coated colour 2700
Fixed spout
Fixed nozzle

Materials in media contact:
Brass
Rubber, EPDM
Silicone based lubricant
PP
SPX (Soft PEX)

Mounting:
½" nut with locking pins, O-ring and washer (See 94G0232)

Inlet / outlet connection:
DN8 hose with G½ female inlet (700mm)
DIN 12 898 hose nozzle

Polypropylene handle

Fixed polypropylene nozzle

ISO228/1 - G½", Union nut

MEDIA CODE XX FOR WATER
ONE MEDIA FITTING
ACCORDING TO EN 13792
*Model shown for WPC

Media	Media description	Media code XX
WPC	Water potable cold	01
WPH	Water potable hot	02
WCF	Water coolant, feed	05
WCR	Water coolant, return	06
WNC	Water non-potable, cold	07
WNH	Water non-potable, hot	08
WRC	River water cold	33

Description: 1-Valve, Bench mounted, 1-Hole, , DIN 12 898 hose nozzle									
							Media: Water		
							Comments:		
							Drawing type: Customer drawing		Weight: 1.277 Kg
Rev.	Pos.	Date	TM No.	Design by	Drawn by:	Change:	Designed by: PEC	Drawn by: PEC	Released on TM No. 03-06-24
brownall Labtap®				This drawing is our property and cannot be given to a third party, copied or otherwise used without our permission. BROEN-LAB A/S.			Format: A3		Drawing No.: XL3308582XX-14E
				Revision 14-01-2011					