

Details:
Rubber sealed headwork open/close 2x360°
3-Zone colour, acc. to EN13792:2002

Fixed spout
Fixed nozzle

Materials in media contact:
Brass
Rubber, EPDM
PP
Silicone based lubricant
SPX (Soft PEX)

Mounting:
1/2" nut with locking pins, O-ring and washer (See 94G0232)

Inlet / outlet connection:
DN8 hose with Ø15mm inlet
DIN 12 898 hose nozzle

Polypropylene handle

Fixed Polypropylene nozzle

Fixed Polypropylene nozzle

MEDIA CODE XX FOR WATER
ONE MEDIA FITTING
ACCORDING TO EN 13792
*Model shown for WPC

Media	Media description	Media code XX
WPC	Water potable cold	01
WPH	Water potable hot	02
WCF	Water coolant, feed	05
WCR	Water coolant, return	06
WNC	Water non-potable, cold	07
WNH	Water non-potable, hot	08
WRC	River water cold	33

Description: 3-Valves, Bench mounted, 1-Hole, Fixed spout, Hose connection										
								Media: Water		
								Comments:		
								Drawing type: Customer drawing		
								Weight: 2.400 Kg		
Rev.	Pos.	Date	TM No.	Design by	Drawn by:	Change:		Designed by: PEC	Drawn by: PEC	
				This drawing is our property and cannot be given to a third party, copied or otherwise used without our permission. BROEN-LAB A/S. Revision 14-01-2011			Released on TM No.		Date (DD-MM-YY): 06-05-21	
							Format: A3		Drawing No.: XL3309482XX-14H	