

Area of Application:
Bench mounted
Hot and cold water

Max. working pressure 10 bar
Temperature range 5°C-65°C

Details:
Rubber sealed headwork open/close 2x360°
3-Zone colour, acc. to EN13792:2002
Divided flow
Swivel spout
Aerator

Materials in media contact:
Brass
Rubber, EPDM
PVDF
Silicone based lubricant
POM
SPX (Soft PEX)

Mounting:
½" nut with locking pins, O-ring and washer (See 94G0232)

Inlet / outlet connection:
DN8 hose with Ø15mm inlet (700mm)
Aerator

Polypropylene handle

ISO228/1 - G½"

SPX hose

Aerator

Ø 15

180

Description: 2-Hand.Mix, Bench mounted, 2-Hole, Swivel spout, Aerator

Media: Hot and cold water

Comments: Divided flow mixer

Drawing type: Customer drawing

Weight: 2.050 Kg

Rev. Pos. Date TM No. Design by Drawn by: Change:

Designed by: VEF Drawn by: VEF Released on TM No. 11-07-25

brownall
Labtap®

This drawing is our property and cannot be given to a third party, copied or otherwise used without our permission. BROEN-LAB A/S.
Revision 14-01-2011

Format: A3 Drawing No.: XL3615582XX-14H

MEDIA CODE XX FOR WATER
TWO HANDLE MIXER
*Model shown for WPC/WPH

Media	Media description	Media code XX
WPC WPH	Water potable cold / hot	39
WNC WNH	Water non-potable cold / hot	40